

Standard Weight Floor Topping Concrete Specification

(As received from Burnco Rock Products Ltd.)

Specifications:

Use: Interior floor topping (1 1/2" depth; 2" preferred depth for

residential applications)

Strength (MPa): 20.0
Slump (mm): 80
Aggregate Size (mm): 10
Cement Type: 10

Mix Proportions (in kg):

 Water:
 175

 Cement:
 200

 Fly Ash:
 60

 Rock:
 950

 Sand:
 960

Total: $2,345 \text{ kg/m}^3$

Admixtures:

Water Reducer: 290 ml/100 kg cement

Please note: To enhance tensile strength 1kg/m3 of Polyfibre could be added. (Some

times referred to by the trade name of "Fibremesh").

Expansion Stripping Specification (Part # 85000)

Material: 3" X 1/4" Polyethylene foam sheet

Base Material: Polyolefin resin

Ingredients: Min. 97% Polyethylene foam &

Max. 3% hydrocarbons

Above are suggested specifications only.

In all cases final specifications are as per product manufacturer!

© HeatLink Group Inc. HeatLink is a registered trademark of HeatLink Group Inc.



Manufactured & Distributed by HeatLink Group Inc. Head Office:
4603E - 13th Street NE
Calgary, AB, T2E 6M3
Toll Free: 1-800-661-5332 Phone: (403) 250-3432
Fax: 1-866-450-1155
Mississauga Office:
1555 Bonhill Road, Unit #7
Mississauga, ON, L5T 1Y5
Toll Free: 1-800-661-5332 Phone: (905) 795-8289
Fax: 1-866-450-1155

Heat Link China

Distributed by Cathy-Links International Phone: 852-25107333 Fax: 852-25107208



Distributed by Jamoni Ltd. Phone: (0506) 24062 Fax: (0506) 24063 Free Phone: 1800-311338



Distributed by Distributora Caisa S.A. de C.V. Phone: (52-55) 5515-9837 (52-55) 5516-5300



Distributed by HeatLink Group Inc. Toll Free: 1-800-661-5332 Fax: 1-800-869-6098