

|   |         |
|---|---------|
| Job or Customer :   |         |
| Location :  |         |
| Engineer :  |         |
| <input type="checkbox"/> Complies with Spec<br><input type="checkbox"/> Alternate | Notes : |
| Contractor :  |         |
| HeatLink Rep :  |         |
| Submitted By :  | Date :  |
| Approved By :   | Date :  |
| P.O. Number :   | Date :  |

**Description**

Adjustable pressure bypass valve kit for 76100 or 76200 series 1-1/4" stainless steel manifolds. This valve prevents a steep rise of the pump head and maintains flow at a stable rate. Also ensures only required amount of circulating water is used for hydronic systems.

**Technical Data**

Material:..... Brass, PEX  
 Adjustment Range:..... 0.05-0.5 bar  
 Operating Temperature:..... 160°F (70°C)  
 Maximum Temperature:..... 230°F (110°C)  
 Minimum Temperature:..... 32°F (0°C)

| Qty | Stk. # | Weight             |
|-----|--------|--------------------|
|     | 76937  | 2.4 lb<br>(1.1 kg) |

**Installation**

Installation must follow all of HeatLink's instructions and guidelines.

**Maintenance**

Maintenance must follow all of HeatLink's instructions and guidelines.

**Related Documents**

- HeatLink Limited Heating Warranty

