

Job or Customer :	
Location :	
Engineer :	
<input type="checkbox"/> Complies with Spec <input type="checkbox"/> Alternate	Notes :
Contractor :	
HeatLink Rep :	
Submitted By :	Date :
Approved By :	Date :
P.O. Number :	Date :

Description


Allows easy access to the manifold through a locking, removable, vented door. Satin coat steel is well suited for painting. Comes with one key lock and one coin/screwdriver lock per door. Space is available for mounting a StatLink® module above the manifold.

Qty	Stk. #	Dimension					# of Locks
		A	B	C	D	E	
	72534	34 ½" (876 mm)	28 ½" (724 mm)	5 ⅞" (149 mm)	36" (915 mm)	30" (762 mm)	2
	72542	42 ½" (1080 mm)	28 ½" (724 mm)	5 ⅞" (149 mm)	44" (1118 mm)	30" (762 mm)	2
	72546	46 ½" (1180 mm)	28 ½" (724 mm)	5 ⅞" (149 mm)	48" (1219 mm)	30" (762 mm)	3

Options

Qty	Stk. #	Description
	71901	Key Lock that can field replace the coin/screwdriver lock of the manifold housing door.

#71901



Technical Data

Specifications

Material - backplate and housing	16 Ga galvanized steel
Material - cover	16 Ga satin coat steel

Installation

Installation must follow all of HeatLink's instructions and guidelines.

Maintenance

Maintenance must follow all of HeatLink's instructions and guidelines.

Related Documents

- L672500 Recessed Manifold Housing Installation Instructions
- HeatLink Limited Heating Warranty

Dimension Diagram

